



CONJUNTOS DE CABLES DE FIBRA

SUBCATEGORÍAS, EJEMPLOS

1. PATCH CORD DE FIBRA
2. PIGTAILS DE FIBRA
3. CONJUNTOS DE CABLES MPO





Fiber Optic Patch Cord, Duplex, Singlemode, LC/UPC to SC/UPC, yellow, 18 m

Product Classification

Regional Availability	EMEA Latin America North America
Portfolio	NETCONNECT®
Product Type	Fiber patch cord, duplex

General Specifications

Color, boot A	Blue
Color, boot B	Blue
Color, connector A	Blue
Color, connector B	Blue
Connector A, quantity	2
Connector B, quantity	2
Interface, Connector A	LC/UPC
Interface, Connector B	SC/UPC
Jacket Color	Yellow
Total Fibers, quantity	2

Dimensions

Cord Length	18 m 59.055 ft
Diameter Over Jacket	1.8 mm 0.071 in

Optical Specifications

Fiber Mode	Singlemode
Fiber Type	OS2



1-2105032-8

Packaging and Weights

Packaging quantity 1

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant



Fiber Optic Pigtail, OM4, LC-pigtail, 900 μ m, LSZH, 2 m, aqua

Product Classification

Regional Availability	Europe Middle East/Africa
Portfolio	CommScope®
Product Type	Fiber pigtail, jacketed

General Specifications

Color, boot A	Beige
Color, connector A	Beige
Connector A, quantity	1
Interface, Connector A	LC/UPC
Jacket Color	Aqua
Total Fibers, quantity	1

Dimensions

Cord Length	2 m 6.562 ft
Diameter Over Jacket	0.9 mm 0.035 in

Optical Specifications

Fiber Mode	Multimode
Fiber Type	OM4
Insertion Loss, maximum, connector A	0.15 dB
Return Loss, minimum, connector A	35 dB

Environmental Specifications

Environmental Space	Low Smoke Zero Halogen (LSZH)
----------------------------	-------------------------------



2160042-2


Packaging and Weights

Packaging quantity 1

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant/Exempted





Singlemode MPO12 (female) to MPO12 (female), Fiber Trunk Cable Assembly, 144-Fiber, B2ca, Method A, Low Smoke Zero Halogen

Product Classification

Regional Availability	Europe
Portfolio	CommScope®
Product Type	Fiber trunk cable assembly
Ordering Note	For lengths greater than 999 ft (304 m), orders must be in meters Minimum length may vary based on cable configuration

General Specifications

Color, boot A	Black
Color, boot B	Black
Color, connector A	Green
Color, connector B	Green
Construction Type	Stranded
Fibers per Subunit, quantity	12
Furcation Color	Yellow
Interface, Connector A	MPO-12/APC
Interface, Connector B	MPO-12/APC
Jacket Color	Yellow
Polarity	Method A
Total Fibers, quantity	144

Dimensions

Cable Assembly Length, minimum (ft)	8
Cable Assembly Length, maximum (ft)	999
Cable Assembly Length, minimum (m)	3
	305




A3GMPMPAM

Cable Assembly Length, maximum (m)

305

Ordering Tree



Mechanical Specifications

Cable Retention Strength, maximum

11.24 lb @ 0 ° | 4.40 lb @ 90 °

Optical Specifications

Fiber Mode

Singlemode

Fiber Type

G.652.D | G.657.A2, TeraSPEED®

Environmental Specifications

Operating Temperature

-10 °C to +60 °C (+14 °F to +140 °F)

EN50575 CPR Cable EuroClass Fire Performance

B2ca

Environmental Space

Low Smoke Zero Halogen (LSZH)

Regulatory Compliance/Certifications

Agency

Classification

CHINA-ROHS

Above maximum concentration value

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

REACH-SVHC

Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS

Compliant/Exempted



Included Products

760239624



A3GMPPMAM

760239624
N-144-MP-8G1-F12YL/B2 - Low Smoke Zero Halogen Riser MPO Trunk Cable, 12 fiber subunits
860638318 - MPO12, ULTRA LOW LOSS, FEMALE, SM, GREEN, 3mm



MEDELLÍN:

PBX. (57) 4 444 2892
Cra 50 GG # 12 sur-116

BOGOTÁ:

Tel. (57) 1 256 0001 / 256 6682
Cra 69 B # 77- 45

www.conectar.com.co